

Distinct color to mask stains for special applications



FEATURES AND BENEFITS:

Masks Stains

Distinctive black color hides stains and provides a contrasting backdrop for identifying lighter colored material.

Offers Exceptional Flexibility

Offers a higher tensile strength compared to both ASTM D6319 and EN 455 standards, allowing the hands to move freely and comfortably while wearing the Microflex MidKnight®.

Provides Firm and Consistent Grip

Fully textured design and non-foaming formula enable wearers to have a firm wet grip when handling objects.

Protects against Type 1 Allergies

Contains no natural rubber latex and powder-free, to help protect wearers from Type I skin allergies, skin irritation and dryness.

Industries

- Automotive
- Emergency Medical Services
- Laboratory
- Law Enforcement
- Life Sciences (*Pharmaceutical, Biopharmaceutical & Medical Devices*)
- Tattoo Artists

Applications

- Analytical testing
- Biotechnologies
- Filtration processes
- Food processing
- Laboratory analysis and testing
- Light assembly tasks
- Light assembly of oil-coated pieces
- Light duty maintenance
- Mechanical repairs
- Paint and spray shops
- Pharmaceutical manufacturing
- Patient examination during transport on EMS vehicles
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	MidKnight®
Material	Nitrile
Color	Black
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Fully Textured
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	MDD 93/42/EEC, PPED 89/686/EEC CATEGORY III, COMPLEX DESIGN, EN 455 1,2 AND 3, EN374-3, EN374-2 LEVEL 2 AQL 1.5, ASTM D6319, EN420 (SIZING FOR SPECIAL PURPOSES), REACH COMPLIANT, TGA, US QSR/FDA 510(K)
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES						TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XXL	
Length (mm)	245	245	245	245	245	245	ASTM D3767/EN 420
Average Palm Width (mm)	80	86	96	107	115	118	
Freedom from Holes (Inspection level I)	1.5 AQL						ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.12) / (mil : 4.7)						ASTM D3767/EN 420
	BEFORE AGING			AFTER AGING			
Ultimate Tensile Strength	27 Mpa			14 Mpa			ASTM D 412-06a
Elongation at Break (%)	> 500			> 400			ASTM D 412-06a
Force at break (N)	10			11			EN 455-2

ORDERING INFORMATION:

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XXL
MIDKNIGHT®	REORDER NO.	MK-296-XS	MK-296-S	MK-296-M	MK-296-L	MK-296-XL	MK-296-XXL

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell (Hong Kong) Limited
Unit 3102-3103, 31/F
Manhattan Place
23 Wang Tai Road
Kowloon Bay, Hong Kong
+852 2185 0600
+852 2856 2155

North America
Ansell Protective Products Inc.
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16



EN 374 EN 374

CE PPE 89/686-0493
MDD 93/42