



www.wearwell.com

Electrically Conductive, Diamond-Plate

Group 785-DP

Electrically Conductive Runner is the ideal floor runner for areas where static prevention is a priority. Can be rolled out for long aisle ways or cut to size for specific workstations. Use Electrically Conductive Runner to protect sensitive equipment or eliminate static annoyance. A grounding snap is included on each mat, and grounding is highly recommended for optimum mat performance. Also recommended: workers should wear heel grounders or shoes with conductive soles for max effectiveness.

- Treated surface drains static electricity from personnel
- Available in Smooth or Diamond-Plate surface pattern
- Overall thickness, Smooth 3/32" (2 mm) or Diamond-Plate 5/32" (4 mm)
- Grounding snap is attached to the corner of each mat (NOTE: Mat must be grounded with a ground cord; workers must wear Heel Grounder or shoes with conductive soles)

Type	Runner
Suitable Environment	Dry
Customization Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	PVC
Recycled	<10%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: 1 x10 ³ - 1x10 ⁶ ohm
Dielectric Strength	Not Available

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
785.532x3CUTDPBK	715411603381	Black	5/32	3' Cut up to 75'	N	SF
785.532x3x75DPBK	715411603527	Black	0.15625	3' x 75'	N	RL