



www.wearwell.com

## Static Dissipative Anti-Fatigue

### Group 791

Static Dissipative Anti-Fatigue is an ideal ergonomic standing solution for manufacturing, pharmaceutical, and commercial areas where static electricity can pose a problem. What makes this product such a standout is the homogeneous carbon layer, which assures the speedy dissipation of static. Add to that our exclusive Nitricell sponge base, and you've got a star performer that lasts for years while providing unparalleled ergonomic benefits. Note: Each mat includes an attached grounding snap. Mat must be grounded with a ground cord [available from Wearwell and workers must wear a heel grounder [also available] or shoes with conductive soles.

- EOS/ESD S7.1:  $1 \times 10^6$  to  $1 \times 10^{10}$
- "Best" sponge base
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness 1/2" (13 mm)

<b>Type</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Dry
<b>Customization Level</b>	C1 - Custom Length
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	PVC Surface With Nitrile Infused Sponge
<b>Recycled</b>	<10%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191
Temperature Range	0 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .62 / Wet: COF = .17
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: RTT= $1 \times 10^6$ to $1 \times 10^{10}$
Dielectric Strength	Not Available

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
791.12x2x3GY	715411441747	Gray	0.5	2' x 3'	Y	EA
791.12x3x5GY	715411442287	Gray	0.5	3' x 5'	Y	EA
791.12x3CUTGY		Gray	0.5	3' Cut up to 75'	N	SF
791.12x3x75GY	715411442454	Gray	0.5	3' x 75'	N	RL
791.12x4CUTGY		Gray	0.5	4' Cut up to 75'	N	SF
791.12x4x75GY	715411443185	Gray	0.5	4' x 75'	N	RL

