



# Twill Jean Wipe

Cotton twill wipe

## Description

The Twill Jean Wipe is a 100% cotton fabric, woven in a 2 x 1 twill construction. The Twill Jean Wipe is very absorbent and has high thermal stability for high temperature applications. The edges are bias cut to prevent unraveling.

## Features and Benefits

- Strong, durable, and absorbent
- Suitable for high temperature applications
- Excellent for surface cleaning or spill pick up
- Available irradiated

## Applicability

The information presented here is applicable to the part numbers shown below as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

TJ-44, TJ-66, TJ-99, TJ-1212, TJ-1717

## Technical Data

Attribute; (units)	Value **	Test Method
Basis weight; (g/m <sup>2</sup> )	190	
Sorbency in water		
Intrinsic; (mL/g)	1.6	IEST-RP-CC004.2, Sec. 7.1
Extrinsic; (mL/m <sup>2</sup> )	300	IEST-RP-CC004.2, Sec. 7.1
Sorptive rate; (seconds)	1.5	
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/m <sup>2</sup> )	0.405	
In isopropanol; (g/m <sup>2</sup> )	0.151	
Specific ions		IEST-RP-CC004.2, Sec. 6.2.2
Sodium; (ppm)	105	
Chloride; (ppm)	10	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.1
P ≥ 0.3µm; (x10 <sup>6</sup> /m <sup>2</sup> )	n/a	
P ≥ 0.5µm; (x10 <sup>6</sup> /m <sup>2</sup> )	80.0	
Fibers > 100µm; (x10 <sup>3</sup> /m <sup>2</sup> )	98.00	IEST-RP-CC004.2, Sec. 5.2

\*\* ND = None detected; levels are below detection limit of test equipment

### Notes:

- 1) Data shown are typical values and should not be used as product specifications.
- 2) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 3) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 02/02/09



P.O. Box 530  
 Spartanburg, SC 29304 USA  
 Phone: +1-864-503-8333  
 Fax: +1-864-503-8444  
 Toll free US, Canada, PR: 1-800-289-5762

**Customer Service**  
 United States: 1-866-855-4682  
 Europe/Asia: +1-864-699-8257  
 e-mail: wipers@contecinc.com  
 www.contecinc.com